


# **POUCH DESICCANT INSERTER**

**CVC 1103H** 

The CVC 1103H Pouch Desiccant Inserter is a compact highly cost-effective means to insert desiccants or oxygen absorbents into a variety of bottles and containers. The system cuts packets from a roll and inserts them into containers at speeds of up to 230 bottles per minute. The CVC 1103H is Siemens PLC controlled with servo motor. Options include 3-color stack light and feed screw for higher speed applications.

## **STANDARD FEATURES**

- · Servo Motor & Siemens PLC Controlled
- Display touchscreen instruction for machine operation is available in multiple languages
- · Capability of recipe storage
- Infeed feed screw system for high speed applications
- Storage and printing of Production Report and Alarm Report
- · Safety guards with automatic machine stop when opened
- · Special heavy duty blades for longer durability
- Flexible adjustments can meet different product bottle heights
- Type 304 stainless steel bin, frame, enclosure panels
- · CE or UL/ CSA standard PC safety guard
- · ISO 9001:2015 certified



CVC 1103H Technical Specifications	
Туре	U4
Productivity	Up to 230 BPM (based on 100ml round bottle and 0.5g, L: 35-38 mm pouch, subject to trial confirmation)
Applicable Size	Pouch Type: R-Type: Paper F-Type: Film Pouch Size Range: Thickness: 3- 10 mm (1/8" to 3/8") Length: 33- 75 mm (1 1/4" to 3") Width: 17- 30 mm (5/8" to 1 1/8")
	Bottle Size Range: Dia.: Ø30- 124 mm (1 <sup>1</sup> /4" to 4 <sup>3</sup> /4") Height:: 50- 220 mm (2" to 8 <sup>1</sup> /2") Bottle opening: Ø20- 100 mm ( <sup>3</sup> /4" to 3 <sup>3</sup> /4")
Power Source	220 V, 50/60 Hz, 1 PH
Power Consumption	900 VA (4 A)
Air Pressure	6 bar (87 psi )
Air Consumption	115 NL/min (4 CFM)
Machine Dimensions (LxWxH)	910 x 985 x 2,270 mm (3'-0" x 3'-3" x 6'-11")
Machine Weight	190 kg (418 lbs)
Noise Level	≤ 70 dB
Technical data contained in this material are not binding and may be subject to change without prior notice.	

# **TECHNICAL SPECIFICATIONS**

## **AVAILABLE OPTIONS**


- · Bottle Feed Screw (Container Format Parts)
- · Bottle Reject System
- · Bottle Reject Verification Check
- · Pouch Desiccant Chute (Pouch Format Parts)
- · Dust Cover of Desiccant Roll
- · 3-Color Stack Light
- · 21 CFR Part 11 Compliance
- · OPC UA for Data Collection




· Pouch Desiccant Cutting and Dispensing Mechanism


# **MACHINE LAYOUTS**

# Top View



## Front View





Technical data contained in this material are not binding and may be subject to change without prior notice.





## **Contact Us**

### USA

10861 Business Drive, Fontana, CA 92337 Phone: +1 (909) 355-0311 www.cvcusa.com; www.cvctechnologies.com sales@cvcusa.com

#### Taiwan-Asia Pacific Headquarters

Phone: +886 (4) 2496-3666 sales@cvctechnologies.com

#### India

Phone: +91 (22) 2562-1242, +91 (22) 2562-1243 sales@cvctechnologies.com

#### China

Phone: +86 (512) 8363-6368 sales@cvctechnologies.com