

BOTTOM LABELERCVC 210



The CVC 210 Bottom Labeler is built to automatically apply pressure sensitive labels onto the bottom of flat and indented containers. The CVC 210 comes standard with a 6" wide belt conveyor and is ideal for contract packagers and manufacturers serving the nutraceutical, food, cosmetic, personal care, and consumer electronic markets. All CVC labelers include our patented SelfSet™ software which utilizes a high frequency encoder for extremely easy setup and wrinkle free labeling at the touch of a button.

STANDARD FEATURES

- SelfSet[™] Auto Adjusting Control System
- Stainless Steel Frame on Lockable Casters
- Stainless Steel Flatbed Conveyor, 6" Wide Endless Green Belt
- Touch Screen HMI
- Label Head with up to \pm 1 mm ($^{1}/_{32}$ ") Accuracy
- Label Sensor for Paper or Opaque Labels
- Capacity: up to 150 Pieces Per Minute (PPM) (subject to our factory trial confirmation)



All CVC labelers include our patented SelfSet™ software which utilizes a high frequency encoder for extremely easy setup and wrinkle free labeling at the touch of a button.

CVC 210 Technical Specifications	
Туре	U1
Productivity	Up to 150 PPM (subject to trial confirmation) Dispense Speed: 24 M/min (78 ft/min)
Applicable Size	Label Length: 15-250 mm (1/2" to 10") Label Width: (dependent on label head type) A:15-80 mm (1/2" to 3") B:15-120 mm (1/2" to 4 3/4") Product Length: 30-260 mm (1 1/4" to 10 1/4") Product Width: 25-150 mm (1" to 6") Product Height: 25-150 mm (1/2" to 6")
Power Source	110/220 V, 50/60 Hz, 1 PH
Power Consumption	350 VA (110V: 3.2 A, 220V: 1.6 A)
Air Pressure	6 bar (87 psi)
Air Consumption	50 NL/min (1.8 CFM) (for optional Lot/Date printer)
Machine Dimensions (LxWxH)	1,440 x 895 x 1470 mm (4'-9" x 2'-11" x 4'-10")
Machine Weight	130kg (287 lbs)
Noise Level	≤ 75 dB

^{*} Machine specifications are subject to change without notice.


TECHNICAL SPECIFICATIONS

AVAILABLE OPTIONS


- · Clear, Metallic or Color Label Sensor
- End to End Transfer Plates
- Infeed and Outfeed Conveyor Extensions (Factory installed only)
- Separator Wheel for Controlled Spacing (Factory installed only)

MACHINE LAYOUTS

Top View



Front View



The dimensions shown are for standard machine. The conveyor can be extended: the length may var y based on selected options. This machine can run independently or be integrated into an automated packaging line. All CVC equipment is covered by a one-year parts warranty. Full Warranty details are included in our equipment proposals or can be found on our website.





Contact Us

USA

10861 Business Drive, Fontana, CA 92337 Phone: +1 (909) 355-0311 www.cvctechnologies.com sales@cvcusa.com

USA East Coast Office

1855 New Highway, Suite C, Farmingdale NY 11735 sales@cvcusa.com

Taiwan-Asia Pacific Headquarters

Phone: +886 (4) 2496-3666 sales@cvctechnologies.com

China/ India

sales@cvctechnologies.com