

F_{20P}

Next-Generation in standard tableting technology





Fette Compacting



Tradition and knowledge

Fette Compacting, founded in 1908, is the world's leading provider of integrated solutions for industrial tablet production, with more than 6,000 machines installed globally. For over 75 years, the company has specialized in high-performance machines for the pharmaceutical, nutraceutical, and chemical industries, continuously setting new standards for quality, innovation, and efficiency. The headquarter is in Schwarzenbek near Hamburg (Germany). With 12 subsidiaries, as well as representatives in more than 50 other countries we make our extensive, oral solid dosage-related expertise available to customers all over the world.

As the only manufacturer of tablet presses with a truly global network, the company operates five interconnected Competence Centers in Germany (Schwarzenbek), China (Nanjing), the US (Rockaway), India (Goa) and Brazil (Campinas).

At the core of the company is the commitment to improving the quality of life for people worldwide through innovative product developments and services. This is encompassed by the company philosophy, 'Together – for quality of life'.



Fette Compacting Nanjing as subsidiary with own production site represents Fette Compacting since 2004.

All the machines and components are made in accordance with German standards, and satisfy the specifications of the American FDA (Food and Drug Administration) regulation authority, as well as the requirements of the international cGMP (Current Good Manufacturing Practices). Fette Compacting delivers all installations with computer-supported controllers that meet the requirements of Title 21 CFR Part 11 (Code of Federal Regulations of the FDA) for electronic documentation.

Service

Efficient machines alone are not enough. Equally important are diverse service offerings. This does not just include maintenance and repair, but also consultancy – especially in performance and operation.

If you are facing challenges in your tablet production, our application specialists are available for you, all over the world. We arrange the perfect solution to minimize machine downtime and to keep your production output up.

Basic Design

The new p Series is distinguished by its cross-generation system compatibility, consistently designed in accordance with the principle of process and system compatibility. For this reason, process-related assemblies are largely unchanged. Accordingly, the p Series retains all features which have made it so valuable for our customers.

F20p single rotary tablet press – remarkable flexibility

With the innovative platform the F20p demonstrate the flexible and efficient concept of modern manufacturing. It is suitable for a wide range of products and batch sizes and thus enables maximum flexibility in your production.





PURE – the most important features of the new p Series at a glance

Being PURE – the base for a strategic partnership in operations

Productive

- + High output in standard operations
- + Boosting tableting production capacity and driving operational excellence





Universal

- + Compatibility and innovation well balanced
- + Minimized re-validation effort
- + Ease of use: managing and operating formulations

Efficient

- + Upgraded energy saving technology - up to 40 %
- + Optimized integration of process equipment and improved intuitive user experience
- + Enhanced cost efficiency





Robust

- Optimized design for intensive utilization and high yields
- + Outstanding lifetime in standard tablet productions







THC/Ont



Rapid and simple product changeover

- + Faster, easier turret changeover including cams and punches
- + Flexible use also of segment or die turrets
- + Flexible compression stations for fast format and product changeover

Operator and cleaning-friendly compression chamber


- + Strict separation of drive elements and measuring points
- + Maximum conformity with GMP guidelines and Easy-to-clean concepts
- + Tool-free design for disassembly of parts
- + Perfect access from all four sides
- + Geometrically optimized surfaces for the easiest possible handling and fast cleaning
- + e-SOP function: Recipe-specific reproducible soft-hardware settings
- + Driving Operational Excellence in standard operations

Segment Technology

- + Up to 25% increase in output
- + 50% reduction of product loss (max.)
- + 88% reduction in manual operations for refitting
- + 100% dimensional accuracy compared to dies













r ficient





Cross-generation compatibility

The F20p is distinguished by its crossgeneration system compatibility, consistently designed in accordance with the principle of process. All process-related components are identical in the previous p Series. This system-compatible design significantly minimizes the efforts associated with machine validation and qualification.

Not only by design, but also related to operating modes – an easy transfer of existing products from the previous p Series to the new F20p is enabled.

E.g. Even critical parameters of product recipes can be transferred from previous p Series models directly to the new F20p with minimal modification and validation.

With slight modifications, existing die turrets can be adopted from the tablet presses of the previous p Series models.

Experience applied to basic design

Fette Compacting has accumulated experience from over 75 years and more than 6,000 installed tablet presses to develop the new generation technological platform on which the electronics and mechanical components are based.

Basic modules optimized based on application experience

Reduce the intermediate interval

E.g. new feed hopper has optimized dimensions and curvature for broader material diversity coverage.

Multiple configurations widely adapted to materials

Validated configuration packages are available as options.

E.g. Kits for: MUPS, thermolabile products, effervescent tablet, chewing gum, ...
















Integrated electrical cabinet

- + IP54 certified
- + Improved dust-tightness: Double-layer cabinet housing with completely sealed internal coverage
- + Less maintenance requirements
- + Dual cooling circuits effectively control internal temperature, even during long term and high-load operation



Dust extraction system

- + Reduced dust exposure
- + Aerodynamically designed dust extraction system with improved efficiency even at low vacuum utilization
- + Easy and fast cleaning through stainless steel parts
- + Preventing cross-contamination



Dust-tight tablet chute with peripheral

- + Easy cleaning, reducing noise levels and dust exposure
- + Clamp connection as standard for optimized connection to peripheral
- + Plug-and-Play design
- + Poka Yoke principle and geometrical similarity of components





Dust-tight tablet chute

+ Innovative dust-tight tablet chute ensures a safe production environment

Energy saving by torque drive

- + Efficient torque drive enhances equipment efficiency and durability
- + Up to 40% power saving compared to previous model









Intuitive user Interface

- + Enables intuitive operations, quality parameter settings and efficient acquisition of real-time data
- + 21 CFR Part 11 compliant
- + Optional: RFID operator login and customized authority management

Digital Ready


- + Compatible across systems, prepared for MES & IoT
- + Real-time data integrity by SQL server database
- + Error-free implementation of standard operating procedures (SOPs)


Smart**Interface**by Fette Compacting


- + 24/7 access to data, documentation and machine real-time monitoring by mobile devices
- + Digital value-added function for easier handling and process acceleration
- + Key performance indicator (KPI) dashboard


Dimensions

Standard floor plan












Foundation loading

Dimensions


Turret exchange floor plan







Service cart 120 kg



Technical Data

| Dies (D) / Segments (S) | | D | D | D | D |
|--|-------|---|--|---|--------------------------------|
| Number of punch stations | | 47 | 43 | 36 | 30 |
| Punch type | | FS19 [®] EU19 FS [®] EU19 BBS | FS19® EU19 FS® EU19 TSM19 BB | FS19 [®] EU19 FS [®] EU19 TSM19 B | EU1" EU1"-441 TSM1" D |
| Tablet output units/h | min. | 42,300 | 38,700 | 32,400 | 27,000 |
| | max. | 338,400 | 309,600 | 259,200 | 180,000 |
| Max. compression force 1* | kN | 100 | 100 | 100 | 100 |
| Max. compression force 2* | kN | 100 | 100 | 100 | 100 |
| Max. tablet diameter | mm | 11 | 13 | 18 | 25 |
| Max. filling depth** | mm | 18 | 18 | 18 | 22 |
| Pitch circle diameter | mm | 410 | 410 | 410 | 410 |
| Turret rotation speed min. | min-1 | 15 | 15 | 15 | 15 |
| max. | min-1 | 120 | 120 | 120 | 100 |
| Die diameter | mm | 22 | 24 | 30,16 | 38,1 |
| Die-/segment height | mm | 22.225 | 22.225 | 22.225 | 23.8 |
| Punch shaft diameter | mm | 19 | 19 | 19 | 25.35 |
| Punch length Upper/lower punch | mm | 133.6 | 133.6 (133.35) | 133.6 (133.35) | 133.6 (133.35) |
| Upper punch insertion depth | mm | 1-4 | 1 – 4 | 1-4 | 1 – 4 |
| $\textbf{Dimensions} \; L \times W \times H$ | mm | 1,200 × 1,545 × 2,080 | | | |
| Weight | | Tablet press approx. 3,2 | 200-3,500 kg, operating t | erminal 100 kg | |
| Electrical supply parameters | | Operating voltage 380- | 480 V, 50/60 Hz, power co | onsumption 12.5 kW *** | |

Theoretical values or technical limits: These can vary in practice, according to product and application. Tablet thickness is a parameter depending on product and can strongly vary.

* limited by punch properties

*** special filling depth available on request

**** 17 kW Maximum power consumption with integrated process equipment

| S | S | S |
|------------------------------------|----------------|----------|
| 45 | 36 | 33 |
| FS19® EU19 FS® EU19 TSM19 | EU1" TSM1" | EU1"-441 |
| 40,500 | 32,400 | 29,700 |
| 324,000 | 216,000 | 198,000 |
| 100 | 100 | 100 |
| 100 | 100 | 100 |
| 18 | 25 | 25 |
| 20 | 20 | 20 |
| 410 | 410 | 410 |
| 15 | 15 | 15 |
| 120 | 100 | 100 |
| - | - | - |
| 25 | 25 | 25 |
| 19 | 25.35 | 25.35 |
| 133.6 (133.35) | 133.6 (133.35) | 133.6 |
| 1 – 4 | 1-4 | 1-4 |
| | | |
| | | |
| | | |

Disclaims: Some features, described in this brochure are optional, subject to individual machine configuration on demand.

© by Fette Compacting GmbH

This publication may not be reprinted in whole or part without our express permission. All right reserved. No rights may be derived from any errors in content or from typographical or typesetting errors. Diagrams, features and dimensions represent the current status on the date of issue of this leaflet. We reserve the right to make technical changes. The visual appearance of the products may not necessarily correspond to the actual appearance in al cases or in every detail.

Fette Compacting GmbH

Grabauer Strasse 24 21493 Schwarzenbek, Germany Phone +49 4151 12-0 Fax +49 4151 3797 tablet@fette-compacting.com

Fette Compacting America, Inc.

400 Forge Way Rockaway N.J. 07866, USA Phone +1 973 5868722 Fax +1 973 5860450 sales@fetteamerica.com

Fette Compacting America Latina Ltda.

Av. Cambacica, 1200 módulo 10 Parque Imperador CEP 13097-160 Campinas / SP, Brazil Phone / Fax +55 19 37969910 contato@fette-compacting.com.br

Fette Compacting Mexico, SA de CV

Adolfo Prieto No. 1638 Colonia Del Valle Sur 03100 Mexico, DF, Mexico Phone +52 55 40000653 tablet@fette-compacting.com

Fette Compacting (China) Co., Ltd.

No. 9 Shengtong Road, Moling Sub-District, Jiangning Development Zone, 211111 Nanjing Jiangsu Province, P.R.C., China Phone +86 25 52121818 Fax +86 25 52129951 fcn@fette-compacting.com

Fette Compacting Machinery India Private Limited

Plot No. S 115, Phase III B Verna Industrial Estate Verna, Goa 403 722, India Phone +91 90498 54568 marketing-in@fette-compacting.com

Fette Compacting Asia Pacific Pte Ltd.

2 Bukit Merah Central #18-01 Singapore 159835, Singapore Phone +65 6371 1556 infoasiapacific@fette-compacting.com

Fette Compacting Ibérica SL

Avenida Labradores, 1 2ª Planta, Oficina 3 28760 Tres Cantos, Spain Phone +34 91 8039689 Fax +34 91 3483052 fcib@fette-compacting.com

Fette Compacting France

2 rue du Centre 93160 Noisy Le Grand, France Phone +33 155 812121 Fax +33 155 812120 fcf@fette-compacting.com

Fette Compacting Belgium BVBA

Schaliënhoevedreef 1b 2800 Mechelen, Belgium Phone +32 15 684260 Fax +32 15 684269 fcbe@fette-compacting.com

EuroPharma Machinery Ltd

Unit 12 Highview Bordon, Hampshire, GU35 0AX United Kingdom Phone +44 1420 473344 Fax +44 1420 488030 admin@europharma.co.uk

Fette Compacting Middle East FZE

Jebel Ali Free Zone, Jafza Lobby 14, Office 308, Dubai United Arab Emirates Phone +971 4 8808226 dubai@fette-compacting.com

Fette Compacting North-West Africa

Tour d'Affaire Nord, Centre Commercial Bab Ezzouar – Regus 4ème Etg. 16000 Algiers, Algeria Phone +213 770 117 007 fcnwa@fette-compacting.com

www.fette-compacting.com

