

SHRINKMASTER

Shrink Packaging Machines

L-Bar Sealer | Side Sealer



L-Bar Sealer and Side Sealer

Applicable Packaging Products:

Cosmetics, shampoo, book, magazine, notebook, stationery, toys, food, vegetable, grocery, kitchenware, daily product, box, bottle, can, drinks, electronics, paper roll, tissue, wire, metal parts, tin, jar... etc.



TY - 7112



TY - 7315H

Servo Motor Touch Panel



TY - 601P

Semi Auto L-Sealer

P: Pneumatic Sealing (Optional Device)



TY - 706

High speed side sealer.
Servo motor touch panel.



TY - 701 - 3000L

Suitable for long shape product.

Min. product length: 600mm

Specification	TY-7008	TY-7112	TY-7212	TY-7315	TY-7315H	TY-701-300H	TY-701-3000L	TY-706-150	TY-601P
Machine Size (L × W × H) mm	1600 × 810 × 1550	2100 × 930 × 1580	2560 × 1130 × 1580	2100 × 930 × 1580	2400 × 1130 × 1630	3030 × 1750 × 1650	4500 × 980 × 1580	2930 × 1900 × 1530	1750 × 700 × 1300
Product Range (L × W × H) mm	(100–300) × (40–230) × (5–80)	(100–500) × (60–330) × (5–120)	(120–700) × (200–500) × (5–120)	(100–450) × (50–300) × (5–150)	(100–450) × (50–300) × (5–150)	(250–600) × (200–400) × (120–300)	(600–3000) × (50–200) × (20–120)	(120–800) × (60–350) × (5–150)	(100–500) × (40–300) × (5–100)
Speed	1–25 packs/min	1–25 packs/min	1–20 packs/min	1–45 packs/min	1–45 packs/min	1–15 packs/min	1–12 packs/min	30–80 packs/min	1–12 packs/min
Power Consumption (kW)	2.2	2.6	3	2.5	2.5	3	3.3	15	4.4
Power Supply	220V / 1P or 380V / 3P / 50–60Hz (as applicable across models)								

- Power supply: 220V, 60Hz, 1P (other power supply available upon request).
- Working height: 750 mm (available upon request).
- Closing conveyor (S) available for products shorter than 100 mm (min. length 30 mm).
- Packaging speed varies depending on film thickness, product size, and operator.
- Clean & filtered compressed air to be provided by the buyer.
- Optional functions and customized machine configurations available upon request.

Product Applications

